




**TECHNICAL SHEET** 

19/11/2025



Assembly bench for fitting perimetral band-cut hardware on aluminium, wood and PVC sashes. A system of drop-away vices grips the sash. The bench is equipped with an automatic feeding screwing system and optionally with a system for hardware cutting and measuring with hydro-pneumatic shears.



### **TECHNICAL SHEET**

19/11/2025



#### **Clamping system**

A retractable vice system under the work bench enables centred clamping of the frame.



### Work bench pneumatic tilting

By means of pneumatic footswitch, it is possible to place the bench in an inclined position from 0° (horizontal) to 12° to facilitate hardware assembly operations.



# Automatic screwing unit

The screwing unit with automatic feed runs on horizontal guides.



# Support surface in hard anti-friction PVC

The anti-friction hard PVC support surface ensures great smoothness of the frame allowing easy handling.







#### FIT MA / MANUAL ASSEMBLY BENCHES

WORK BENCHES	
Hard anti-friction PVC contact surface	•
Pneumatic tilting of work table from 0° (horizontal) to 12°	•
Adjustable work table height (mm)	875 ÷ 925
Topas-able not table in girk (i.i.i.)	

WORKPIECE LOCKING	
Vice opening (mm)	290 ÷ 2.840
Adjustable clamping force, max. (N)	740
Self-centring clamping system with retractable bars	•

CHARACTERISTICS	
Automatic screwing unit mounted on horizontal guide with laser positioning system	•
Belt hardware cutting with automatic stop gauge	0
Air consumption (NI/min)	870
Installed power (kW)	0,35
Length (mm)	3.540
Width (mm)	1.640
Load capacity (kg)	1.960
Weight (kg)	300

Included • Available O