



TECHNICAL SHEET

10/12/2025



Stop gauge and profile support system, driven by DC motor, complete with electronic read-out through encoder.




TECHNICAL SHEET

10/12/2025



Side view

Through special steel bracket, the mechanical connection to the cutting machine is made precisely and rigidly.



Roller

PVC-coated steel rollers of 295 mm that allow the profile to slide effectively, preventing surface damage



Reference stop

Carriage running on ball bushing actuated by numerically controlled kinematics, which allows, referring to the centre of the blade, the realization of the length of the workpiece to be cut.



Control

The control console allows total management of the machine's operational functions. Through the PCL tool, it is possible to perform the preparation of cutting lists, then allowing the repositioning of the stop sequentially and automatically.



Barcode reader (Optional)

Through the use of the barcode reader, the system automatically identifies the structure and consequently positions the stop at the predetermined height, reducing cycle times.

Emmegi S.p.A. Via delle Industrie, 2 20044 - Arese (MI) ITALY Tel 39 02356961 P.IVA 01978870366 info@tekna.it www.tekna.it The right to make technical alterations is reserved.









MICROBO / SINGLE HEAD CUTTING-OFF MACHINES

•
•
•
•
0
0

MACHINE CHARACTERISTICS	
PVC-coated steel rollers (295) on bearings	•
Pneumatic lifting of workpiece stop	•
Effective stroke (according to model) (mm)	4.200 ; 7.200

Included • Available O