



## **TKE 124**

### Corner Crimping Machines



Crimping machine for pressing large profiles and curtain walls, with the highest quality requirements. Its main strengths are: ease of configuration and use, with set-up and adjustment times reduced to a minimum; the extreme robustness of the structure that gives high precision to the processing; the great pressing force is provided by a large-volume bellows cylinder that does not require maintenance.

**TKE 124 / CORNER CRIMPING MACHINES****CHARACTERISTICS**

Nominal pressure (bar)	7
Standard power supply	230V / 1~ / 50Hz
Max crimping force (kN)	70
Max crimping force (kg)	7.000
Max crimping height (mm)	140 ; 200

**DIMENSION AND WEIGHT**

Packing dimensions LxHxP (mm)	1.100 x 950 x 1.230
Weight (kg)	550

**ACCESSORIES**

Standard bracing clamp 30 mm	<input checked="" type="radio"/>
Aluminium bracing clamp of 8 mm	<input checked="" type="radio"/>
Self regulating bracing clamp	<input type="radio"/>
Support profiles	2
Pair of standard knives, 3 mm	<input checked="" type="radio"/>
Pair of standard knives, 4 mm	<input checked="" type="radio"/>
Pair of standard knives, 7 mm	<input checked="" type="radio"/>
Pair of standard knives, 5 mm	<input type="radio"/>
Pair of standard knives, 8 mm	<input type="radio"/>
Pair of standard knives, 10 mm	<input type="radio"/>
Standard adjustable knives, 3 mm - 5 ÷ 15 mm chamber offset	<input checked="" type="radio"/>
Standard adjustable knives, 3 mm - 15 ÷ 35 mm chamber offset	<input type="radio"/>
Special knives for 5 ÷ 15 mm chamber offset	<input type="radio"/>
Special knives for 15 ÷ 35 mm chamber offset	<input type="radio"/>

Included ● Available ○