
TKE 124

CORNER CRIMPING MACHINES



Crimping machine for pressing large profiles and curtain walls, with the highest quality requirements. Its main strengths are: ease of configuration and use, with set-up and adjustment times reduced to a minimum; the extreme robustness of the structure that gives high precision to the processing; the great pressing force is provided by a large-volume bellows cylinder that does not require maintenance.

Emmegi S.p.A.
Via Archimede, 10
41019 - Limidi di Soliera (MO)
ITALY

Tel +39 059 895411
Fax +39 059 566286
P.Iva/C.Fisc 01978870366
info@emmegi.com
www.emmegi.com

The right to make technical alterations is reserved.

TKE 124 / CORNER CRIMPING MACHINES

CHARACTERISTICS

Nominal pressure (bar)	7
Standard power supply	230V / 1~ / 50Hz
Max crimping force (kN)	70
Max crimping force (kg)	7.000
Max crimping height (mm)	140 ; 200

DIMENSION AND WEIGHT

Packing dimensions LxHxP (mm)	1.100 x 950 x 1.230
Weight (kg)	550

ACCESSORIES

Standard bracing clamp 30 mm	●
Aluminium bracing clamp of 8 mm	●
Self regulating bracing clamp	○
Support profiles	2
Pair of standard knives, 3 mm	●
Pair of standard knives, 4 mm	●
Pair of standard knives, 7 mm	●
Pair of standard knives, 5 mm	○
Pair of standard knives, 8 mm	○
Pair of standard knives, 10 mm	○
Standard adjustable knives, 3 mm - 5 ÷ 15 mm chamber offset	●
Standard adjustable knives, 3 mm - 15 ÷ 35 mm chamber offset	○
Special knives for 5 ÷ 15 mm chamber offset	○
Special knives for 15 ÷ 35 mm chamber offset	○

Included ● Available ○

Emmegi S.p.A.
Via Archimede, 10
41019 - Limidi di Soliera (MO)
ITALY

Tel +39 059 895411
Fax +39 059 566286
P.Iva/C.Fisc 01978870366
info@emmegi.com
www.emmegi.com

The right to make technical alterations is reserved.