




TKE 330 SA-MA

Single Head Cutting-Off
Machines



Troncatrice monotesta a lama ascendente prevista per tagli a 90°, 45° destro e sinistro ed angolazioni intermedie.




Blade

The cutting-off machine is equipped with a 300-mm cemented carbide blade mounted on a manually actuated feed system.



Vices

The machine is equipped with a horizontal and vertical vice assembly, which are pneumatically actuated in the S version, and manually actuated in the M version.



Cutting zone

The sturdy cast-iron horizontal support surface, with its vertical square rigidly coupled to it, forms the workpiece clamping area, which features a large bearing area for optimum clamping of workpieces.


**TKE 330 SA-MA / SINGLE HEAD CUTTING-OFF MACHINES****BLADE**

Made of Widia (mm)

Ø = 300

BLADE FEED

Manual

CUTTING DIAGRAM**CUTTING AREA PROTECTION**

Local, manually controlled

LUBRICATION SYSTEM

Manual

PROFILE POSITIONING

Manual workpiece reference stop

WORKPIECE LOCKING

Manual or pneumatic vertical vice (according to model)

1

Horizontal manual vice

1



MOTOR

Three-phase brakemotor	<input checked="" type="radio"/>
Brake intervention time (s)	10
Power (kW)	1,5

Included ☒ Available ☐