



Transit KT

Trolleys



Trolley for transportation and storage of casement and finished door/ window frames. The resting base has rollers for easier handling of heavy or large size pieces.



Side contact surfaces

All contact surfaces are coated with soft nonslip PVC, which ensures the integrity of the surfaces in the housing stages.



Door sliding roller conveyor

A fixed roller conveyor allows horizontal translation of the frame by stem-mounted rollers that ensure smoothness and ease of movement.



Pivoting wheels

Equipped with 2 fixed wheels and 2 pivoting wheels with brake, which ensure a high degree of mobility and object handling ease. Locking the braking units allows their position to be fixed near different work areas.



TRANSIT KT / TROLLEYS

CHARACTERISTICS

Number of compartments (based on model)	5 - 6 - 10 - 15
Compartment width (mm) (based on model)	100 - 130 - 160
Compartment depth (mm)	1.160
Preparation for K-Rail track	●
Base with roller conveyor	●
Soft PVC contact surface	●
Handle for moving	●
4 swivel casters, 2 of which have locking stops (mm)	Ø = 150

WEIGHT (DEPENDING ON MODEL)

TRANSIT KT 10-160 mm (kg)	190
TRANSIT KT 5-160 mm (kg)	100
TRANSIT KT 15-130 mm (kg)	230
TRANSIT KT 10-130 mm (kg)	160
TRANSIT KT 6-100 mm (kg)	105
TRANSIT KT 10-100 mm (kg)	160
TRANSIT KT 15-100 mm (kg)	225
TRANSIT KT 5-130 mm (kg)	95

MAXIMUM LOAD CAPACITY (ACCORDING TO MODEL)

TRANSIT KT 6-100 mm (kg)	600
TRANSIT KT 10-100 mm (kg)	740
TRANSIT KT 15-100 mm (kg)	675
TRANSIT KT 5-130 mm (kg)	500
TRANSIT KT 10-130 mm (kg)	740
TRANSIT KT 15-130 mm (kg)	670
TRANSIT KT 5-160 mm (kg)	500
TRANSIT KT 10-160 mm (kg)	710

Included ● Available ○