



Transit KA

Trolleys



Trolley for transportation and storage of sashes. The base of each compartment is equipped with rolls for easier handling of heavy or large size pieces.



Side contact surfaces

All contact surfaces are coated with soft nonslip PVC, which ensures the integrity of the surfaces in the housing stages.



Door sliding roller conveyor

A fixed roller conveyor allows horizontal translation of the frame by stem-mounted rollers that ensure smoothness and ease of movement.



Pivoting wheels

Equipped with 2 fixed wheels and 2 pivoting wheels with brake, which ensure a high degree of mobility and object handling ease. Locking the braking units allows their position to be fixed near different work areas.





TRANSIT KA / TROLLEYS

DEPTH (BASED ON MODEL)

TRANSIT KA 6-100 mm (mm)	995
TRANSIT KA 10-100 mm (mm)	1.540
TRANSIT KA 15-100 mm (mm)	2.220
TRANSIT KA 5-130 mm (mm)	1.010
TRANSIT KA 10-130 mm (mm)	1.840
TRANSIT KA 15-130 mm (mm)	2.670
TRANSIT KA 5-160 mm (mm)	1.160
TRANSIT KA 10-160 mm (mm)	2.140

CHARACTERISTICS

Number of compartments (based on model)	5 - 6 - 10 - 15
Compartment width (mm) (based on model)	100 - 130 - 160
Compartment depth (mm)	980
Soft PVC contact surface	●
Preparation for K-Rail track	●
Base with roller conveyor	●
Handle for moving	●
4 swivel casters, 2 of which have locking stops (mm)	Ø = 150

WEIGHT (DEPENDING ON MODEL)

TRANSIT KA 10-160 mm (kg)	180
TRANSIT KA 5-160 mm (kg)	95
TRANSIT KA 15-130 mm (kg)	220
TRANSIT KA 10-130 mm (kg)	155
TRANSIT KA 5-130 mm (kg)	90
TRANSIT KA 15-100 mm (kg)	215
TRANSIT KA 10-100 mm (kg)	150
TRANSIT KA 6-100 mm (kg)	100



MAXIMUM LOAD CAPACITY (ACCORDING TO MODEL)

TRANSIT KA 5-130 mm (kg)	500
TRANSIT KA 6-100 mm (kg)	600
TRANSIT KA 10-100 mm (kg)	750
TRANSIT KA 15-100 mm (kg)	685
TRANSIT KA 10-130 mm (kg)	745
TRANSIT KA 15-130 mm (kg)	680
TRANSIT KA 5-160 mm (kg)	500
TRANSIT KA 10-160 mm (kg)	720

Included ● Available ○